

[Technical boards]

RIBERA DE ZORROZAURRE 15 2º  
48014 BILBAO  
SPAIN  
[WWW.FOREST-TRAFFIC.COM](http://WWW.FOREST-TRAFFIC.COM)  
+34 94 475 74 02  
+34 94 475 74 03

### DESCRIPTION

#### DEFINITION

WATERPROOF PANEL WITH 100% BIRCH CORE. IT PRESENTS ONE EXTERIOR FACE WITH ANTI-SLIP RUBBER AND ANOTHER FACE (INCLUDING EDGES) SEALED WITH CHLORINE-RUBBER BLACK PAINT.

#### GLUING

CLASS III (EN 314-2) / RUBBER FIXED BY PUR GLUES

#### COLOR / FINISH

RUBBER / BLACK

#### FORMATS

THICKNESS (MM)	DIMENSIONS (MM)
FROM 6 TILL 89	FROM 2440 *1220 TILL 3100 *1525



### CHARACTERISTICS

	UNIT	VALUE	STANDARDS
DENSITY	KG/M <sup>3</sup>	750 ± 50	UNE-EN 323
MODULUS OF ELASTICITY	LONGITUDINAL	>9.500 MPA	UNE-EN 310
	TRANSVERSE	>7.200 MPA	UNE-EN 310
RESISTANCE OF ELASTICITY	LONGITUDINAL	>95 MPA	UNE-EN 310
	TRANSVERSE	>80 MPA	UNE-EN 310
RESISTANCE TO UNSTUCK	MPA	96,5	UNE-EN ISO 178
ABSORPTION OF WATER AT 20º	%	2,31	UNE-EN ISO 62
RESISTANCE TO UNSTUCK BY TRACTION	N	2330	ASTM C 297
HUMIDITY	%	7,1	UNE-EN 322
RESISTANCE TO BOOTING SCREWS	DAN	198	UNE-EN 13446
DETERMINATION OF THE HEAT OF COMBUSTION	MJ/KG	18,24	UNE-EN ISO 1716

\* INDICATED DATA ARE BASED ON THE TESTS REALISED IN THE INDEPENDENT LABORATORIES.

\* THESE DATA ARE BASED IN SPECIFIC THICKNESSES OF THE CORE AND THE PLATES, THEREFORE THEY HAVE TO BE TAKEN ON THE ACCOUNT ONLY AS ORIENTATION.