

DESCRIPTION

DEFINITION

WATERPROOF TRIPLY PANEL 100% FIR

GLUING

CLASS III (EN 314-2)

COLOR / FINISH

VARNISHED IN YELLOW

FORMATS

THICKNESSES	DIMENSIONS
27 MM	FROM 1970 * 500 TILL 2000 * 1000



DEFECTS

UNEVEN SURFACE (GAPS BETWEEN THE 3 PLYS)	NO PERMITTED
SEPARATIONS	NO PERMITTED
HOLES	DIAMETR <= 10 MM. HAVE TO BE REPAIRED WITH FILLERS DIÁMETRO > 10 MM. NO PERMITTED
QUALITY OF THE CORNERS	STRAIGHT
STAINS OF GLUE	PERMITTED
ADHESIONS BETWEEN PLYS	NO PERMITTED

TOLERANCIAS DIMENSIONALES

ITEM	NOMINAL	TOLERANCE	
LENGTH (MM)	2000	+2 (>1000)	
	1970		
	1000	+1 (<=1000)	
	970		
WIDTH (MM)	500	+1	
THICKNESS (MM)	27	+/- 0,5	
CROSS LENGTH (MM)	2000 * 500 * 27	> 2061	3
		<= 2061	4
	1970 * 500 * 27	> 2032	3
		<= 2032	4
1000 * 500 * 27	> 1118	3	
	<= 1118	4	
970 * 500 * 27	> 1091	3	
	<= 1091	4	

FISICAL AND MECHANICAL PROPERTIES

ITEM	PANEL
HUMEDAD	8%-12%

* INDICATED DATA ARE BASED ON THE TESTS REALISED IN THE INDEPENDENT LABORATORIES.

* THESE DATA ARE BASED IN SPECIFIC THICKNESSES OF THE CORE AND THE PLATES, THEREFORE THEY HAVE TO BE TAKEN ON THE ACCOUNT ONLY AS ORIENTATION.